



Tapernaben Taper hubs



Anschraubnaben – Bolt on hubs

| Bezeichnung Part No. | Material | Taper- Buchse Taper bush | DA (mm) | DT (mm) | D + 0/- 0,1 (mm) | DK (mm) | B (mm) | b (mm) | Z (mm) | BM (mm) | d (mm) | Gewicht o. Buchse Weight without bush (≈ kg) |
|-------------------------|----------|-----------------------------------|------------|------------|------------------------|------------|-----------|-----------|-----------|------------|-----------|---|
| SM 12 | GG | 1210 | 180 | 135 | 90 | 75 | 25 | 6,5 | 2,5 | 11,5 | 6 x 7,5 | 1,5 |
| SM 16 | GG | 1615 | 200 | 150 | 110 | 85 | 38 | 7,5 | 2,5 | 12,5 | 6 x 7,5 | 3,0 |
| SM 20 | GG | 2012 | 270 | 190 | 140 | 110 | 32 | 8,5 | 2,5 | 13,5 | 6 x 9,5 | |
| SM 25 | GG | 2517 | 340 | 240 | 170 | 125 | 45 | 9,5 | 2,5 | 14,5 | 8 x 11,5 | 7,6 |
| SM 30-1 | GG | 3020 | 430 | 300 | 220 | 160 | 51 | 13,5 | 2,5 | 18,5 | 8 x 13,5 | 16,6 |
| SM 30-2 | GG | 3020 | 485 | 340 | 250 | 160 | 51 | 13,5 | 2,5 | 18,5 | 8 x 13,5 | 20,5 |

Einschweißnaben Type WM – Weld on hubs type WM

| Bezeichnung Part No. | Material | Taper- Buchse Taper bush | DA (mm) | D + 0/- 0,05 (mm) | DK (mm) | B + 0,5/- 0,05 (mm) | b1 (mm) | b2 (mm) | Gewicht o. Buchse Weight without bush (≈ kg) |
|-------------------------|----------|-----------------------------------|------------|-------------------------|------------|---------------------------|------------|------------|---|
| WM 1210 | St | 1210 | 70 | 60 | 58 | 25 | 9 | 10 | 0,3 |
| WM 1615 | St | 1615 | 83 | 70 | 68 | 38 | 16 | 11 | 0,6 |
| WM 2012 | St | 2012 | 95 | 90 | 88 | 32 | 12 | 12 | 0,7 |
| WM 2517 | St | 2517 | 127 | 110 | 108 | 44 | 19 | 13 | 1,8 |
| WM 3030 | St | 3030 | 152 | 130 | 125 | 76 | 25 | 19 | 3,5 |
| WM 3535 | St | 3535 | 184 | 155 | 151 | 89 | 32 | 25 | 10,0 |
| WM 4040 | St | 4040 | 225 | 195 | 187 | 102 | 32 | 32 | 13,2 |
| WM 4545 | St | 4545 | 254 | 220 | 213 | 115 | 38 | 38 | 20,1 |
| WM 5050 | St | 5050 | 276 | 242 | 228 | 127 | 38 | 38 | 25,4 |

Einschweißnaben Type WH – Weld on hubs type WH

| Bezeichnung Part No. | Material | Taper- Buchse Taper bush | DA (mm) | D + 0/- 0,05 (mm) | DK (mm) | B + 0,5/- 0,05 (mm) | b1 (mm) | b2 (mm) | Gewicht o. Buchse Weight without bush (≈ kg) |
|-------------------------|----------|-----------------------------------|------------|-------------------------|------------|---------------------------|------------|------------|---|
| WH 1210 | St | 1210 | 70 | 65 | 64,5 | 25 | 9 | 10 | 0,3 |
| WH 1610 | St | 1610 | 80 | 75 | 74,5 | 25 | 9 | 10 | |
| WH 2012 | St | 2012 | 95 | 90 | 89,5 | 32 | 12 | 12 | |
| WH 2517 | St | 2517 | 115 | 110 | 109,5 | 44 | 19 | 15 | |
| WH 3020 | St | 3020 | 145 | 140 | 139,5 | 50 | 19 | 15 | 2,7 |
| WH 3525 | St | 3525 | 190 | 180 | 179,5 | 65 | 25 | 25 | |
| WH 3535 | St | 3535 | 190 | 180 | 179,5 | 89 | 32 | 25 | 10,0 |
| WH 4040 | St | 4040 | 200 | 190 | 189,5 | 101 | 32 | 30 | |
| WH 4545 | St | 4545 | 210 | 200 | 199,5 | 115 | 40 | 30 | |
| WH 5050 | St | 5050 | 230 | 220 | 219,5 | 127 | 40 | 35 | |

| Taper-Buchse Taper bush | 1210 | 1610 | 1615 | 2012 | 2517 | 3020 | 3030 | 3525 | 3535 | 4040 | 4545 | 5050 |
|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|--------|--------|
| Bohrung d ₂ (mm) von ... bis ... Bore d ₂ (mm) from ... to ... | 11-32 | 14-42 | 14-42 | 14-50 | 16-60 | 25-75 | 35-75 | 35-90 | 35-90 | 40-100 | 44-110 | 70-125 |