



### Breitkeilriemen – flankenoffen, formgezahnt nach USA-Standard RMA/MPTA

### Moulded Cogged, Raw Edge Variable Speed Belts to USA Standard RMA/MPTA



Riemen-Nr. Belt no.			
1422 V 235	1926 V 290	2830 V 396	3432 V 528
1422 V 240	1926 V 407	2830 V 422	3432 V 534
1422 V 270	1926 V 415		
1422 V 290	1926 V 427	2926 V 471	4036 V 541
1422 V 300		2926 V 486	4036 V 574
1422 V 330	2230 V 266	2926 V 521	
1422 V 340	2230 V 273	2926 V 546	4430 V 530
1422 V 360	2230 V 275	2926 V 574	4430 V 548
1422 V 400	2230 V 326	2926 V 586	4430 V 555
1422 V 420	2230 V 375	2926 V 606	4430 V 560
1422 V 440		2926 V 616	4430 V 570
1422 V 460	2322 V 329	2926 V 636	4430 V 578
1422 V 470	2322 V 347	2926 V 646	4430 V 600
1422 V 480	2322 V 364	2926 V 666	4430 V 610
1422 V 540	2322 V 396	2926 V 686	4430 V 630
1422 V 600	2322 V 421	2926 V 726	4430 V 652
1422 V 660	2322 V 434	2926 V 750	4430 V 660
	2322 V 441	2926 V 776	4430 V 670
1430 V 215	2322 V 461	2926 V 786	4430 V 690
	2322 V 481		4430 V 700
1922 V 277	2322 V 486	3226 V 392	4430 V 710
1922 V 282	2322 V 521	3226 V 400	4430 V 730
1922 V 298	2322 V 541	3226 V 433	4430 V 750
1922 V 321	2322 V 601	3226 V 450	4430 V 790
1922 V 332	2322 V 661	3226 V 505	4430 V 800
1922 V 338	2322 V 681	3226 V 545	4430 V 850
1922 V 363	2322 V 701	3226 V 585	
1922 V 381	2322 V 801	3226 V 603	4436 V 525
1922 V 386		3226 V 650	4436 V 551
1922 V 403	2426 V 353	3226 V 663	4436 V 561
1922 V 426	2426 V 363	3226 V 723	4436 V 576
1922 V 443		3226 V 783	4436 V 646
1922 V 454		3226 V 843	4436 V 750
1922 V 460	2530 V 500		
1922 V 484	2530 V 530		
1922 V 526	2530 V 560	3230 V 419	
1922 V 544	2530 V 600	3230 V 528	
1922 V 604	2530 V 630	3230 V 560	
1922 V 630	2530 V 670	3230 V 585	
1922 V 646	2530 V 710	3230 V 600	
1922 V 666	2530 V 750	3230 V 630	
1922 V 686	2530 V 790	3230 V 670	
1922 V 706	2530 V 800	3230 V 710	
1922 V 721	2530 V 934	3230 V 723	
1922 V 726	2530 V 990	3230 V 750	
1922 V 751		3230 V 800	
1922 V 756		3230 V 850	
	2830 V 337		
	2830 V 363		
	2830 V 366	3432 V 450	
1926 V 250	2830 V 367	3432 V 456	
1926 V 275	2830 V 393	3432 V 480	

**Erklärung Interpretation**  
 1422 V 235  
 14 = obere Breite top width 14/16"  
 22 = Winkel pulley angle degrees  
 V = Variable Speed Variable Speed  
 235 = Wirklänge in pitch length in 1/10"