

Rippenband Ribbed Belts

Profil Sect.	PH	PJ
e = (mm)	1,6	2,34
h ≈ (mm)	2,5	3,50



Profil Section PH

Bezugslänge Effective length	
(mm)	(Zoll inch)
698	27,50
735	28,90
762	30,00
813	32,00
858	33,80
864	34,00
886	34,90
955	37,60
965	38,00
975	38,40
990	39,00
1016	40,00
1080	42,50
1092	43,00
1096	43,10

Bezugslänge Effective length	
(mm)	(Zoll inch)
1168	46,00
1194	47,00
1200	47,20
1222	48,10
1230	48,40
1262	49,70
1270	50,00
1285	50,60
1290	50,80
1301	51,20
1309	51,50
1316	51,80
1321	52,00
1333	52,50
1371	54,00

Bezugslänge Effective length	
(mm)	(Zoll inch)
1397	55,00
1439	56,70
1475	58,10
1600	63,00
1854	73,00
1895	74,60
1915	75,40
1930	76,00
1956	77,00
1992	78,40
2083	82,00
2155	84,80

Gewicht Belt weight: 1 Rippe rib ≈ 0,005 kg/m


Profil Section PJ

Bezugslänge Effective length	
(mm)	(Zoll inch)
280	11,00
330	13,00
356	14,00
362	14,30
381	15,00
406	16,00
414	16,30
432	17,00
457	18,00
483	19,00
508	20,00
559	22,00
584	23,00
610	24,00
660	26,00
711	28,00
723	28,50
737	29,00
762	30,00
813	32,00
836	32,90
864	34,00
914	36,00
955	37,60
965	38,00
1016	40,00
1092	43,00
1105	43,50
1110	43,70
1123	44,20
1130	44,50
1150	45,30

Bezugslänge Effective length	
(mm)	(Zoll inch)
1168	46,00
1194	47,00
1200	47,30
1222	48,10
1244	49,00
1262	49,70
1270	50,00
1285	50,60
1301	51,20
1309	51,50
1316	51,80
1321	52,00
1333	52,50
1355	53,40
1371	54,00
1397	55,00
1428	56,20
1439	56,70
1475	58,10
1549	61,00
1600	63,00
1651	65,00
1663	65,50
1752	69,00
1780	70,00
1854	73,00
1895	74,60
1910	75,20
1915	75,40
1930	76,00
1956	77,00
1965	77,40



Bezugslänge Effective length	
(mm)	(Zoll inch)
1981	78,00
1992	78,40
2083	82,00
2155	84,80
2210	87,00
2337	92,00
2489	98,00

Weitere Abmessungen auf Anfrage. Further sizes on request.



Rippenband Ribbed Belts


Profil Sect.	PK
e = (mm)	3,56
h ≈ (mm)	4,60



Profil Section PK


Bezugslänge Effective length	
(mm)	(Zoll inch)
630	24,80
648	25,50
698	27,50
730	28,70
775	30,50
800	31,50
812	32,00
830	32,70
865	34,00
875	34,50
890	35,00
913	36,00
920	36,20
940	37,00
954	37,60
962	37,80
990	39,00
1015	40,00
1080	42,50
1090	43,00
1125	44,30
1150	45,30
1165	45,90
1190	46,80
1200	47,20
1222	48,10
1230	48,40
1245	49,00
1270	50,00
1285	50,60
1290	50,80
1321	52,00
1330	52,40
1345	53,00
1371	54,00
1397	55,00
1439	56,70
1460	57,50
1520	59,80
1560	61,40
1570	61,80
1600	63,00
1655	65,20
1690	66,50
1755	69,10
1854	73,00
1885	74,20
1930	76,00
1956	77,00
1980	78,00
2030	79,90
2050	80,70
2080	82,00
2120	83,50
2145	84,40
2170	85,40

Bezugslänge Effective length	
(mm)	(Zoll inch)
2235	88,00
2255	88,80
2362	93,00
2460	96,90
2515	99,00
2845	112,00



Rippenband Ribbed Belts

Profil Sect.	PL	PM
e = (mm)	4,7	9,4
h ≈ (mm)	7,0	13,0



Profil Section PL

Bezugslänge Effective length	
(mm)	(Zoll inch)
954	37,50
991	39,00
1075	42,30
1194	47,00
1270	50,00
1333	52,50
1371	54,00
1397	55,00
1422	56,00
1562	61,50
1613	63,50
1664	65,50
1715	67,50
1764	69,50
1803	71,00
1841	72,50
1943	76,50
1981	78,00
2020	79,50
2070	81,50
2096	82,50
2134	84,00
2197	86,50
2235	88,00
2324	91,50
2362	93,00
2476	97,50
2515	99,00
2705	106,50
2743	108,00

Bezugslänge Effective length	
(mm)	(Zoll inch)
2845	112,00
2895	114,00
2921	115,00
2997	118,00
3086	121,50
3124	123,00
3289	129,50
3327	131,00
3492	137,50
3696	145,50
4051	159,50
4191	165,00
4470	176,00
4622	182,00
5029	198,00
5385	212,00
6096	240,00

Profil Section PM

Bezugslänge Effective length	
(mm)	(Zoll inch)
2286	90,00
2388	94,00
2515	99,00
2693	106,00
2832	111,50
2921	115,00
3010	118,50
3124	123,00
3327	131,00
3531	139,00
3734	147,00
4089	161,00
4191	165,00
4470	176,00
4648	183,00
5029	198,00
5410	213,00
6121	241,00

Bezugslänge Effective length	
(mm)	(Zoll inch)
6883	271,00
7646	301,00
8408	331,00
9169	361,00
9931	391,00
10693	421,00
12217	481,00
13741	541,00
15266	601,00

Weitere Abmessungen auf Anfrage. Further sizes on request.