



Materiale C 45 E • Material C45 E • Matière C 45 E • Materiel C 45 E - UNI EN 10083-1
Dimensioni valide per gruppo non precaricato - Dimensions before mounting

Nostro codice Our code Unser Kode Notre code Nuestro código	Dimensioni / Dimentions / Dimensions Abmessungen / Dimensiones						Serraggio / Blocking power Force de blocage / Befestigungskraft Fuerza de bloqueo			Sbloccaggio / Unblocking Deblocage / Freigabe Desbloqueo		Coppie trasmissibili / Torque Couple / Drehmoment / Par			
	d	D	H	H1	H2	H3	NV	Tv (Nm)	N°Viti / Screws / Vis Schraubenanzahl Tornillos	NV	N°Viti / Screws / Vis Schraubenanzahl Tornillos	Mt (Nm)	Pa (N/mm ²)	Ta (KN)	Pm (N/mm ²)
200s019	19	47	45	39	26	31	M6x25	17	4	M6	2	353	228	30,6	98
200s020	20	47	45	39	26	31	M6x25	17	4	M6	2	382	226	33,4	98
200s022	22	47	45	39	26	31	M6x25	17	4	M6	2	431	215	33,4	93
200s024	24	50	45	39	26	31	M6x25	17	6	M6	3	519	215	50,2	102
200s025	25	50	45	39	26	31	M6x25	17	6	M6	3	578	225	50,2	102
200s028	28	55	45	39	26	31	M6x25	17	6	M6	3	686	215	50,2	107
200s030	30	55	45	39	26	31	M6x25	17	6	M6	3	745	196	50,2	117
200s032	32	60	45	39	26	31	M6x25	17	8	M6	4	912	225	66,9	111
200s035	35	60	45	39	26	31	M6x25	17	8	M6	4	1010	196	66,9	116
200s038	38	65	45	39	26	31	M6x25	17	8	M6	4	1216	205	66,9	121
200s040	40	65	45	39	26	31	M6x25	17	8	M6	4	1323	196	66,9	122
200s042	42	75	55	47	30	36	M8x30	41	6	M8	3	2128	232	66,9	137
200s045	45	75	55	47	30	36	M8x30	41	6	M8	3	2304	232	92,1	137
200s048	48	80	55	47	30	36	M8x30	41	6	M8	3	2461	213	110,0	132
200s050	50	80	55	47	30	36	M8x30	41	6	M8	3	2530	213	122,8	132
200s055	55	85	55	47	30	36	M8x30	41	8	M8	4	3138	218	122,8	142
200s060	60	90	55	47	30	36	M8x30	41	8	M8	4	3314	194	122,8	153
200s065	65	95	55	47	30	36	M8x30	41	8	M8	4	4079	208	122,8	137
200s070	70	110	67	57	40	46	M10x35	83	8	M10	4	6707	220	193,5	140
200s075	75	115	72	62	40	46	M10x35	83	8	M10	4	7354	205	193,5	135
200s080	80	120	72	62	40	46	M10x35	83	8	M10	4	7943	196	193,5	127
200s085	85	125	72	62	40	46	M10x35	83	10	M10	4	9512	205	241,9	142
200s090	90	130	72	62	40	46	M10x35	83	10	M10	4	10100	196	241,9	135
200s095	95	135	72	62	40	46	M10x35	83	10	M10	4	11865	205	241,9	145
200s100	100	145	89	77	46	52	M12x45	145	8	M12	4	15396	211	282,8	145
200s110	110	155	89	77	46	52	M12x45	145	8	M12	4	16867	192	282,8	136
200s120	120	165	89	77	46	52	M12x45	145	10	M12	4	22064	211	353,6	152
200s130	130	180	89	77	46	52	M12x45	145	12	M12	4	23535	192	424,3	137
200s140	140	190	98	84	51	59	M14x45	230	8	M14	4	30210	192	448,5	142
200s150	150	200	98	84	51	59	M14x45	230	10	M14	5	36440	201	489,0	150