



Materiale C 45 E • Material C45 E • Matière C 45 E • Materiel C 45 E - UNI EN 10083-1

Dimensioni valide per gruppo non precaricato - Dimensions before mounting

Nostro codice Our code Unser Kode Notre code Nuestro código	Dimensioni / Dimentions / Dimensions Abmessungen / Dimensiones							Serraggio / Blocking power / Force de blocage Befestigungskraft / Fuerza de bloqueo			Sbloccaggio Unblocking Deblocage Freigabe		Coppie trasmissibili / Torque Couple / Drehmoment / Par			
	d	D	D1	H	H1	H2	H3	NV	Tv (Nm)	N°Viti / Screws / Vis Schraubenanzahl Tornillos	Desbloccamiento		Mt (Nm)	Pa (N/mm ²)	Ta (KN)	Pm (N/mm ²)
											NV	N°Viti				
225s114	14	55	62	38	30	17	22	M8 x 25	42	4	M8	2	290	460	40	110
225s116	16	55	62	38	30	17	22	M8 x 25	42	4	M8	2	330	400	40	110
225s118	18	55	62	38	30	17	22	M8 x 25	42	4	M8	2	370	360	40	110
225s119	19	55	62	38	30	17	22	M8 x 25	42	4	M8	2	390	340	40	110
225s120	20	55	62	38	30	17	22	M8 x 25	42	4	M8	2	410	320	40	110
225s122	22	55	62	38	30	17	22	M8 x 25	42	4	M8	2	450	290	40	110
225s124	24	55	62	38	30	17	22	M8 x 25	42	4	M8	2	490	270	40	110
225s125	25	55	62	38	30	17	22	M8 x 25	42	4	M8	2	510	260	40	110
225s128	28	55	62	38	30	17	22	M8 x 25	42	4	M8	2	570	230	40	110
225s130	30	55	62	38	30	17	22	M8 x 25	42	4	M8	2	610	220	40	110
225s224	24	65	72	38	30	17	22	M8 x 25	42	5	M8	3	610	330	50	120
225s225	25	65	72	38	30	17	22	M8 x 25	42	5	M8	3	640	320	50	120
225s228	28	65	72	38	30	17	22	M8 x 25	42	5	M8	3	710	290	50	120
225s230	30	65	72	38	30	17	22	M8 x 25	42	5	M8	3	770	270	50	120
225s232	32	65	72	38	30	17	22	M8 x 25	42	5	M8	3	820	250	50	120
225s233	33	65	72	38	30	17	22	M8 x 25	42	5	M8	3	850	240	50	120
225s235	35	65	72	38	30	17	22	M8 x 25	42	5	M8	3	890	230	50	120
225s238	38	65	72	38	30	17	22	M8 x 25	42	5	M8	3	970	210	50	120
225s240	40	65	72	38	30	17	22	M8 x 25	42	5	M8	3	1020	200	50	120
225s330	30	80	87	41	33	20	25	M8 x 25	42	7	M8	3	1070	320	70	110
225s332	32	80	87	41	33	20	25	M8 x 25	42	7	M8	3	1140	300	70	110
225s333	33	80	87	41	33	20	25	M8 x 25	42	7	M8	3	1180	280	70	110
225s335	35	80	87	41	33	20	25	M8 x 25	42	7	M8	3	1250	270	60	110
225s338	38	80	87	41	33	20	25	M8 x 25	42	7	M8	3	1350	250	60	110
225s340	40	80	87	41	33	20	25	M8 x 25	42	7	M8	3	1420	240	70	110
225s342	42	80	87	41	33	20	25	M8 x 25	42	7	M8	3	1500	230	70	110
225s345	45	80	87	41	33	20	25	M8 x 25	42	7	M8	3	1600	210	60	110
225s348	48	80	87	41	33	20	25	M8 x 25	42	7	M8	3	1710	200	70	110
225s350	50	80	87	41	33	20	25	M8 x 25	42	7	M8	3	1780	190	60	110