



Materiale C 45 E • Material C45 E • Matière C 45 E • Materiel C 45 E - UNI EN 10083-1

Dimensioni valide per gruppo non precaricato - Dimensions before mounting

Nostro codice Our code Unser Kode Notre code Nuestro código	Dimensioni / Dimentions / Dimensions Abmessungen / Dimensiones						Serraggio / Blocking power Force de blocage / Befestigungskraft Fuerza de bloqueo			Sbloccaggio Unblocking Deblocage Freigabe Desbloqueo		Coppie trasmissibili / Torque Couple / Drehmoment / Par			
	d	D	D1	H	H1	H2	NV	Tv (Nm)	N°Viti / Screws / Vis Schraubenanzahl Tornillos	NV	N°Viti	Mt (Nm)	Pa (N/mm <sup>2</sup> )	Ta (KN)	Pm (N/mm <sup>2</sup> )
400s025	25	55		46	40	32	M6 x 35	17,5	6	M6	3	750	250	70	130
400s028	28	55		46	40	32	M6 x 35	17,5	6	M6	3	830	220	70	120
400s030	30	55		46	40	32	M6 x 35	17,5	6	M6	3	890	210	70	120
400s035	35	60		60	54	44	M6 x 45	17,5	7	M6	3	1220	150	80	90
400s038	38	75		62	54	44	M8 x 50	42	7	M8	3	2270	240	130	120
400s040	40	75		62	54	44	M8 x 50	42	7	M8	3	2390	230	130	140
400s042	42	75		62	54	44	M8 x 50	42	7	M8	3	2510	220	130	120
400s045	45	75		62	54	44	M8 x 50	42	7	M8	3	2690	200	130	120
400s048	48	80		72	64	56	M8 x 55	42	8	M8	4	3270	220	150	130
400s050	50	80		72	64	56	M8 x 55	42	8	M8	4	3410	170	150	110
400s055	55	85		72	64	56	M8 x 55	42	9	M8	4	4220	170	170	110
400s060	60	90		72	64	56	M8 x 55	42	10	M8	4	5110	170	180	120
400s065	65	95		72	64	56	M8 x 55	42	10	M8	4	5540	160	190	110
400s070	70	110		88	78	70	M10 x 60	85	10	M10	4	10150	200	310	130
400s075	75	115		88	78	70	M10 x 60	85	10	M10	4	10870	190	320	120
400s080	80	120		88	78	70	M10 x 60	85	11	M10	4	12760	190	340	130
400s085	85	125		88	78	70	M10 x 60	85	12	M10	5	14790	200	380	140
400s090	90	130		88	78	70	M10 x 60	85	12	M10	5	15660	190	380	130
400s095	95	135		88	78	70	M10 x 60	85	12	M10	5	16530	180	380	130
400s100	100	145		112	100	90	M12 x 80	145	12	M12	4	23250	180	510	120
400s110	110	155		112	100	90	M12 x 80	145	12	M12	5	27900	170	530	130
400s120	120	165		112	100	90	M12 x 80	145	14	M12	6	35510	190	650	140
400s130	130	180		130	116	104	M14 x 90	235	12	M14	5	45130	180	770	130
400s140	140	190		130	116	104	M14 x 90	235	14	M14	7	56700	190	870	140
400s150	150	200		130	116	104	M14 x 90	235	15	M14	7	65090	190	940	140
400s160	160	210		130	116	104	M14 x 90	235	16	M14	7	74060	190	1000	150
400s170	170	225		164	148	134	M16 x 120	360	14	M16	7	95240	170	1220	130
400s180	180	235		164	148	134	M16 x 120	360	16	M16	7	108050	170	1290	130
400s190	190	250		164	148	134	M16 x 120	360	16	M16	7	121650	170	1360	130
400s200	200	260		164	148	134	M16 x 120	360	16	M16	7	128060	160	1350	130
400s220	220	285		164	148	134	M16 x 120	360	18	M16	8	158470	170	1580	130