



Materiale C 45 E • Material C45 E • Matière C 45 E • Materiel C 45 E - UNI EN 10083-1

Dimensioni valide per gruppo non precaricato - Dimensions before mounting

Nostro codice Our code Unser Kode Notre code Nuestro código	Dimensioni / Dimentions / Dimensions Abmessungen / Dimensiones						Serraggio / Blocking power Force de blocage / Befestigungskraft Fuerza de bloqueo			Coppie trasmissibili / Torque Couple / Drehmoment / Par		
	d	D	D1	H	H1	H2	NV	Tv (Nm)	N°Viti / Screws / Vis Schraubenzahl Tornillos	Mt (Nm)	Pa (N/mm <sup>2</sup> )	Ta (KN)
603s024	24	50	19	23	19,5	14	M5 x 18	4,9	6	170	286	15,0
			20							210		18,5
			21							250		21,0
603s030	30	60	24	25	21,5	16	M5 x 18	4,9	7	300	233	15,7
			25							340		23,7
			26							380		26,7
603s036	36	72	28	27,5	23,5	18	M6 x 20	11,8	5	440	307	27,0
			30							570		38,0
			31							630		43,0
603s044	44	80	34	29,5	25,5	20	M6 x 20	11,8	7	620	317	44,0
			35							780		49,0
			36							860		54,0
603s050	50	90	38	31,5	27,5	22	M6 x 25	11,8	8	940	289	48,8
			40							1160		58,8
			42							1380		69,0
603s055	55	100	42	34,5	30,5	23	M6 x 25	11,8	8	1160	252	48,0
			45							1520		61,7
			48							1880		77,0
603s062	62	110	48	34,5	30,5	23	M6 x 25	11,8	10	1850	279	69,0
			50							2200		80,9
			52							2400		90,0
603s068	68	115	50	34,5	30,5	23	M6 x 25	11,8	10	2000	255	71,2
			55							2500		80,9
			60							3150		95,7
603s075	75	138	55	37,8	32,5	25	M8 x 30	29,4	7	2500	273	94,4
			60							3200		111,0
			65							3950		126,0
603s080	80	145	60	37,8	32,5	25	M8 x 30	29,4	7	3200	256	99,3
			65							3900		115,0
			70							4600		130,0
603s090	90	155	65	44,3	39	30	M8 x 35	29,4	10	4750	271	141,0
			70							6000		160,0
			75							7250		178,0
603s100	100	170	70	49,3	44	34	M8 x 35	29,4	12	6900	258	163,0
			75							7500		182,0
			80							9000		202,0
603s110	110	185	75	56,4	50	39	M10 x 40	57,8	9	7200	244	185,0
			80							9000		207,0
			85							10800		221,0
603s125	125	215	85	60,4	54	42	M10 x 40	57,8	12	11000	266	240,0
			90							13000		262,0
			95							15000		285,0
603s140	140	230	95	68	60,5	46	M12 x 45	98	10	15100	264	308,0
			100							17600		331,0
			105							20100		357,0
603s155	155	265	105	72	64,5	50	M12 x 50	98	12	22000	263	366,0
			110							25000		392,0
			115							28000		417,0
603s165	165	290	115	81	71	56	M16 x 55	245	8	31000	277	513,0
			120							35000		544,0
			125							39000		564,0